

FIBER OPTIC ACCESSORIES

# ST STYLE CERAMIC FIBER CONNECTOR



## Description

ORCA® connectors are designated and manufactured with an ISO9001 system. A complete line of fiber connectors for any telecommunications application. Available in Multimode and Single-mode version. Available connector styles include MT-RJ, SC, ST, LC and FC. Feature connectors with ceramic ferrules. Most standard connectors are in stock for immediately ship, special and bulk packages are available and we make quickly on request.



### Feature:

High performance, pre-radius ceramic ferrule	Anaerobic epoxy compatible
ST Style compatible coupling	For 125µm cladding diameter
Available in multimode or singlemode	Including 900µm and 3mm boots
Field installable	ROHS Compliant

Connectors are designed and tested to conform the requirements of IEC 60874-14, CECC BFOC 86260, EIA/TIA and Telcordia (Bellcore) documents for connectors.

### Product Facts:

Typical insertion loss:	<0,3dB
Temperature Range:	-30°C to +70°C
Durability:	500 Cycles
Ferrule Type:	Ceramic
Body material:	Nichel plated Brass

The stated values are reflecting the connector's abilities; anyhow, the exact values are absolutely depending on the accuracy of the termination, installation, and finale testing, as well as the handling of the used test equipment.

### Ordering Information code:

ST MultiMode (MOQ 10 Pz.)	
OC-FCE-130221-01	ORCA - ST SPX Connector MultiMode whit 3,0/0,9mm black boot
ST SingleMode (MOQ 10 Pz.)	
OC-FCE-130223-01	ORCA - ST SPX Connector SingleMode whit 3,0/0,9mm yellow boot

Specifications subject to change without prior notice - For more details please visit www.orca.it