



## NWA90AX

### 802.11ax (WiFi 6) Dual-Radio PoE Access Point

The NWA90AX is truly the right choice for SMB users looking to upgrade to 11ax (WiFi 6) access points without an expensive price tag. It supports WiFi 6 in both 2.4 GHz and 5 GHz frequencies, which is aimed to empower you to enjoy all the best things WiFi 6 has to offer such as faster speeds even when congested or in high-density environments, expanded range in your wireless network, and increased capacity for IoT deployments.

In addition, with the support of captive portal and IEEE 802.1x authentication, the NWA90AX not only offers SMB users the enterprise-level security to protect their business networks, but also the flexible opportunity to customize wireless network usage login for marketing and business recognition.

The NWA90AX with NebulaFlex offers the flexible manageability for you to freely choose between the local GUI management or onboarding to our super easy Nebula cloud management interface that helps you set up your wireless network in minutes.



Dual-radio (dual 2x2) 802.11ax AP provides maximum data rate of 1800 Mbps



Captive portal and IEEE 802.1X authentication support provides enterprise-level security



NebulaFlex allows users to switch between standalone or intuitive Nebula cloud managed modes as needed



Advanced Cellular Coexistence minimizes interferences from 4G/5G cellular networks



Smart Mesh automatically forms dynamic wireless links and mitigates complex, inconvenient cabling WiFi deployments

## Benefits

### Bringing next generation WiFi within reach

WiFi 6 made tremendous improvement by introducing new technologies such as orthogonal frequency-division multiple access (OFDMA), and spatial re-use, which is also referred to as Basic Service Set (BSS) coloring. It aims to satisfy the all requirements from rapidly growing mobile users simultaneously. Zyxel's new NWA90AX is a true WiFi 6 access point which supports essential 11ax functions that delivers faster performance and massive increased-capacity make the user experience even better.

Apart from running at 25% faster speed, NWA90AX can also maximize the WiFi efficiency by allowing simultaneous data transmission for multiple clients; thus, the air time contention is no longer an issue here.

### 4G/5G cellular network coexistence


With the exponential growth of mobile devices in the wireless network, users start to experience degraded performance, such as ping drops and high latency; users have to reduce the use of their mobile devices in order to maintain a smooth, working wireless service. Thus, to enable 4G/5G cellular network coexistence and minimize interference from 4G/5G antennas or signal boosters, the NWA90AX has built-in 4G/5G interference filters. As a result, the visible or invisible 4G/5G indoor antennas in the environment is no longer an issue when installing APs.

### NebulaFlex – simply manage it your way!

The NebulaFlex provides extended flexibility, allowing users to easily switch between standalone and our intuitive cloud-managed NCC (Nebula Control Center) mode any time according to your needs without additional cost while protecting wireless technology investments.

The Nebula cloud management platform provides centralized control and visibility over all Nebula networking devices. Simply you only need to register the device on NCC, and it will automatically join, auto provision and begin to give real-time information. The intuitive platform allows you to group your access points together, control centrally, gain access to diagnostics tools and additional features like captive portal all under a single platform.

## Specifications

<b>Model</b>	<b>NWA90AX</b>	
<b>Product name</b>	802.11ax (WiFi 6) Dual-Radio PoE Access Point	
		
<b>Wireless</b>		
<b>Standard</b>	IEEE 802.11 ax/ac/n/g/b/a	
<b>MIMO</b>	MU-MIMO	
<b>Wireless speed</b>	<b>2.4 GHz</b>	575 Mbps
	<b>5 GHz</b>	1200 Mbps
<b>Frequency band</b>	<b>2.4 GHz</b>	<ul style="list-style-type: none"> <li>• USA (FCC): 2.412 to 2.462 GHz</li> <li>• Europe (ETSI): 2.412 to 2.472 GHz</li> </ul>
	<b>5 GHz</b>	<ul style="list-style-type: none"> <li>• USA (FCC): 5.15 to 5.35 GHz; 5.470 to 5.850 GHz</li> <li>• European (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHz</li> </ul>
<b>Bandwidth</b>	20-, 40-, 80-MHz	
<b>Conducted typical transmit output power*1 (limited by local regulatory requirements)</b>	<b>US (2.4 GHz/5 GHz)</b>	23/26 dBm
	<b>EU (2.4 GHz/5 GHz)</b>	20/25 dBm
<b>RF Design</b>		
<b>Antenna type</b>	Internal antenna	
<b>Antenna gain</b>	<b>2.4 GHz</b>	3 dBi, 2x2: 2SS
	<b>5 GHz</b>	4 dBi, 2x2: 2SS
<b>Minimum receive sensitivity</b>	Min. Rx sensitivity up to -99 dBm	
<b>WLAN Feature</b>		
<b>Band steering</b>	Yes	
<b>WDS/Mesh*2</b>	Yes	
<b>Fast roaming</b>	Pre-authentication, PMK caching, and 802.11r/k/v	
<b>DCS</b>	Yes	
<b>Load balancing</b>	No	
<b>Security</b>		
<b>Encryption</b>	WEP/WPA/WPA2-PSK/WPA3	
<b>Authentication</b>	WPA/WPA2-Enterprise/EAP/IEEE 802.1X/RADIUS authentication	
<b>Access management</b>	L2-isolation/MAC filtering/Rogue AP detection	
<b>Networking</b>		
<b>IPv6</b>	Yes	
<b>VLANs</b>	Yes	
<b>WMM</b>	Yes	
<b>U-APSD</b>	Yes	

\*1: Conducted typical transmit output power excludes antenna gain. For total (EIRP) transmit power, add antenna gain.

\*2: WDS, ZyMesh, Smart Mesh and Industry's Open Mesh, Easy Mesh are different mesh systems that do not work with one another.

<b>Model</b>		NWA90AX
<b>Management</b>		
<b>Operating mode</b>	Cloud managed/standalone	
<b>ZON Utility</b>	<ul style="list-style-type: none"> <li>• Discovery of Zyxel switches, APs and gateways</li> <li>• Centralized and batch configurations <ul style="list-style-type: none"> <li>▪ IP configuration</li> <li>▪ IP renew</li> <li>▪ Device reboot</li> <li>▪ Device locating</li> </ul> </li> <li>▪ Web GUI access</li> <li>▪ Firmware upgrade</li> <li>▪ Password configuration</li> </ul>	
<b>Web UI/CLI</b>	Yes	
<b>SNMP</b>	No	
<b>Physical Specifications</b>		
<b>Item</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	140 x 140 x 37.5/5.51 x 5.51 x 1.48
	<b>Weight (g/lb.)</b>	290/0.64
<b>Packing</b>	<b>Dimensions (WxDxH)(mm/in.)</b>	240 x 155 x 60/9.45 x 6.10 x 2.36
	<b>Weight (g/lb.)</b>	600/1.32
<b>Included accessories</b>	<ul style="list-style-type: none"> <li>• Power adapter</li> <li>• Mount plate</li> <li>• Mounting screws</li> </ul>	
<b>MTBF (hr)</b>	1,010,980	
<b>Physical Interfaces</b>		
<b>Ethernet port</b>	1 x 10/100/1000M LAN	
<b>Power</b>	<ul style="list-style-type: none"> <li>• Power adapter: AC 100 - 240 V - 50/60 Hz 0.3 A; Output: DC +12 V 1.5 A</li> <li>• PoE (802.3at): power draw 16 W</li> </ul>	
<b>Environmental Specifications</b>		
<b>Operating</b>	<b>Temperature</b>	0°C to 50°C/32°F to 122°F
	<b>Humidity</b>	10% to 90% (non-condensing)
<b>Storage</b>	<b>Temperature</b>	-40°C to 70°C/-40°F to 158°F
	<b>Humidity</b>	10% to 90% (non-condensing)
<b>Certifications</b>		
<b>Radio</b>	FCC Part 15C, FCC Part 15E; ETSI EN 300 328, EN 301 893; LP0002, EN 60601-1-2	
<b>EMC</b>	FCC Part 15B, EN 301 489-1; EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, BSMI CNS13438	
<b>Safety</b>	EN 60950-1, IEC 60950-1; BSMI CNS14336-1	

For more product information, visit us on the web at [www.zyxel.com](http://www.zyxel.com)

Copyright © 2023 Zyxel and/or its affiliates. All rights reserved.  
All specifications are subject to change without notice.

